

New ProCinema System is an Affordable Miracle!

New ProCinema 600 Sub/Sat System

Definitive's new ProCinema 600 System is our new entry-level 6-piece home theater system. Its surprisingly affordable price belies its remarkable sophistication. The ProCinema 600 System incorporates the same new technologies and advancements, including BDSS drivers, pure aluminum dome tweeters, planar mediate passive radiators and a 250-watt SuperCube technology powered subwoofer, which have made the new ProCinema 800 and 1000 systems instant mega hits.

The satellites and center channel are available in high-gloss hand-rubbed piano gloss black (with matching black subwoofer) or gloss white. The satellites can be shelf-mounted with their unique tri-lobed base, wall-mounted using the built-in keyhole mount or optional pivot mount or stand-mounted with their optional floor stands. The center channels have an adjustable foot for shelf-mounting or can be wall-mounted using their built-in threaded inserts.

Sonically, the new ProCinema 600 System is a revelation in terms of achieving incredible sound at an affordable price. Their imaging is absolutely boxless, spacious and three-dimensional while delivering pinpoint specificity and localization when called for. They are velvety smooth with a you-are-there presence which is unique at any price and unheard of in this price range. The 600 system is dynamic but capable of great subtlety so it excels equally with music or movies.

SPECIFICATIONS:

ProMonitor 600: Dimensions: 7" H x 4 $\frac{1}{4}$ " D x 4" W. Frequency Response: 65 Hz – 30 kHz. Driver Complement: One 3 $\frac{1}{4}$ " bass/midrange driver coupled to one 3 $\frac{1}{4}$ " pressure-driven planar low-frequency radiator. One 1" pure aluminum dome tweeter. Rec. Assoc. Ampl.: 10 – 150 watts/channel. Frequency Response: 65 Hz – 30 kHz.

ProCenter 600: Dimensions: 4" H x 4 $\frac{1}{4}$ " D x 10 $\frac{1}{2}$ " W. Frequency Response: 55 Hz – 30 kHz. Driver Complement: Two 3 $\frac{1}{4}$ " bass/midrange drivers coupled to two 3 $\frac{1}{4}$ " pressure-driven planar low-frequency radiator. One 1" pure aluminum dome tweeter.

ProSub 600: Dimensions: 13" H x 13" D x 10 $\frac{3}{8}$ " W. Frequency Response: 22 Hz – 150 Hz. Driver Complement: One 8" woofer with polymer cone, one 8" infrasonic radiator. Amplifier: 250 watts RMS. Speaker Level High-Pass Filter: 6 dB/octave (100 Hz). High-Level Low-Pass Filter: 24 dB/octave continuously variable (40 Hz – 150 Hz).



ProCinema 600

Definitive Technology[®]
The Leader in High-Performance Loudspeakers[®]